

---

**Declaration of Performance (DoP) in acc. with**

**Construction Products (Amendment etc.) (EU Exit) Regulations 2019 (No. 465)  
Construction Products (Amendment etc.) (EU Exit) Regulations 2020 (No. 1359)**

**No. ILGS275N-UKCA-10025-01112022**

---

1. Unique identification code of the product Type:

**Plate S275N / 1.0490 in accordance with EN 10025-3**

2. Intended use(s):

**Metallic structure, metallic- / concrete composite construction**

3. Name, registered trade name or registered trademark and contact address of the manufacturer:

**Ilseburger Grobblech GmbH  
Veckenstedter Weg 10  
38871 Ilseburg, Germany  
Tel.: +49 (0) 39452 85 - 0  
Fax: +49 (0) 39452 85 - 8161  
[www.ilseburger-grobblech.de](http://www.ilseburger-grobblech.de)**

4. Name and contact address of the authorised representative whose mandate covers the tasks:

**- not applicable -**

5. System or systems of assessment and verification of constancy of performance of the construction product:

**System 2+**

6. Declaration of performance concerning a construction product covered by a harmonised standard:

**Approved Body - TÜV UK Ltd (No. UKAB 0879) - performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control in accordance with annex ZA of EN 10025-1:2004.**



7. Declared Performance:

Essential characteristic	Performance						Harmonised technical specification
Tolerances on dimensions and shape	see supplementary sheet 1						<b>EN 10025-1:2004</b>
Yield strength	Nominal thickness (mm)		Values (MPa)				
	>	≤	≥				
		16	275				
	16	40	265				
	40	63	255				
	63	80	245				
	80	100	235				
	100	150	225				
	150	200	215				
	200	250	205				
Tensile strength	Nominal thickness (mm)		Values (MPa)				
	>	≤	≥		≤		
		100	370		510		
	100	200	350		480		
	200	250	350		480		
Elongation	Nominal thickness (mm)		Values (%)				
	>	≤	≥				
		16	24				
	16	40	24				
	40	63	24				
	63	80	23				
	80	200	23				
	200	250	23				
Impact energy	Nominal thickness (mm)		Values (J) Temp. (°C)				
			+20	0	-10	-20	
		≤	≥				
	250	55	47	43	40		
Weldability	Nominal thickness (mm)		CEV (%)				
	>	≤	≤				
		63	0,40				
	63	100	0,40				
	100	250	0,42				



Essential characteristic	Performance					Harmonised technical specification
Durability	Nominal thickness (mm)		Ladle analysis (%)			EN 10025-1:2004
		≤		≥	≤	
		250	C		0,18	
			Si		0,40	
			Mn	0,50	1,50	
			P		0,030	
			S		0,025	
			Nb		0,05	
			V		0,05	
			Al ges.	0,02		
			Ti		0,05	
			Cr		0,30	
			Ni		0,30	
			Mo		0,10	
	Cu			0,55		
	N		0,015			

The performance of the product named above is in conformity with the declared performances.  
This declaration of performance is issued under the sole responsibility of the above-mentioned manufacturer.

Signed for and on behalf of the manufacturer by:

Ilseburg, 01.11.2022

**Dipl.-Ing. Andreas Rost**  
Head of Order Management and Technical Service