
Declaration of Performance (DoP) in acc. with

**Construction Products (Amendment etc.) (EU Exit) Regulations 2019 (No. 465)
Construction Products (Amendment etc.) (EU Exit) Regulations 2020 (No. 1359)**

No. ILGS460N-UKCA-10025-01112022

1. Unique identification code of the product Type:

Plate S460N / 1.8901 in accordance with EN 10025-3

2. Intended use(s):

Metallic structure, metallic- / concrete composite construction

3. Name, registered trade name or registered trademark and contact address of the manufacturer:

**Ilsenburger Grobblech GmbH
Veckenstedter Weg 10
38871 Ilsenburg, Germany
Tel.: +49 (0) 39452 85 - 0
Fax: +49 (0) 39452 85 - 8161
www.ilsenburger-grobblech.de**

4. Name and contact address of the authorised representative whose mandate covers the tasks:

- not applicable -

5. System or systems of assessment and verification of constancy of performance of the construction product:

System 2+

6. Declaration of performance concerning a construction product covered by a harmonised standard:

Approved Body -TÜV UK Ltd (No. UKAB 0879) - performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control in accordance with annex ZA of EN 10025-1:2004.



7. Declared Performance:

Essential characteristic	Performance				Harmonised technical specification	
Tolerances on dimensions and shape	see supplementary sheet 1				EN 10025-1:2004	
Yield strength	Nominal thickness (mm)		Values (MPa)			
	>	≤	≥			
		16	460			
	16	40	440			
	40	63	430			
	63	80	410			
	80	100	400			
	100	150	380			
	150	200	370			
200	250	370				
Tensile strength	Nominal thickness (mm)		Values (MPa)			
	>	≤	≥	≤		
		100	540	720		
	100	200	530	710		
200	250	510	690			
Elongation	Nominal thickness (mm)		Values (%)			
	>	≤	≥			
		16	17			
	16	40	17			
	40	63	17			
	63	80	17			
80	200	17				
200	250	16				
Impact energy	Nominal thickness (mm)		Values (J) Temp. (°C)			
			+20	0	-10	-20
		≤	≥			
	250	55	47	43	40	
Weldability	Nominal thickness (mm)		CEV (%)			
	>	≤	≤			
		63	0,53			
	63	100	0,54			
100	250	0,55				



Essential characteristic	Performance					Harmonised technical specification
Durability	Nominal thickness (mm)		Ladle analysis (%)			EN 10025-1:2004
		≤		≥	≤	
		250	C		0,20	
			Si		0,60	
			Mn	1,00	1,70	
			P		0,030	
			S		0,025	
			Nb		0,05	
			V		0,20	
			Al ges.	0,02		
			Ti		0,05	
			Cr		0,30	
			Ni		0,80	
			Mo		0,10	
	Cu			0,55		
	N		0,025			

The performance of the product named above is in conformity with the declared performances.
This declaration of performance is issued under the sole responsibility of the above-mentioned manufacturer.

Signed for and on behalf of the manufacturer by:

Ilseburg, 01.11.2022

Dipl.-Ing. Andreas Rost
Head of Order Management and Technical Service